

EVG



ZSCHIMMER & SCHWARZ

Chemistry tailor-made

A New Synthetic Ester Product Technology Is Now Available

EsterTec vicinal secondary polyol (VSP) esters offer exceptional performance based on their innovative structure achieved via a unique production process. Utilizing standard raw materials that are globally accessible, these esters ensure high stability through vicinal ester molecular positioning. Steric hindrance enhances oxidative stability, while secondary alcohols on adjacent carbons significantly improve hydrolytic stability. Experience the next level of synthetic lubricant performance by formulating with EsterTec VSP diesters.



EsterTec VSP: Best-in-Class Synthetic Lubricant Base Stock Designed for Outstanding Performance Value and Reliability

With a broad viscosity range and operating temperature window (-40°C to 200°C), EsterTec affords superior control of friction and reduces wear, ensuring the stability and long life of highperformance lubricants. This advanced component is miscible with PAO and petroleum base stocks, as well as compatible with standard elastomers and seals. EsterTec excels in heat transfer, features excellent dielectric properties, and exhibits high flash and fire points for enhanced safety in both lubricant and electrical insulating fluid applications. Environmentally friendly, with a high biogenic content, EsterTec is readily biodegradable and USDA BioPreferred, making it a top choice for those seeking efficiency and sustainability on their ESG scorecard.

Benefit From All the Performance Advantages of a Diester or Polyol Ester, Plus Exceptional Benefits That Set This Technology Apart:

- Natural Energy Efficiency: Leverage their low density, high viscosity index (VI), and superior lubricity, for enhanced energy savings.
- Best-in-Class Stability: Enjoy an unparalleled combination of oxidative, thermal, and hydrolytic stability, optimized for extended product life and consistent performance in applications that experience high temperatures or water ingress.
- Optimal Heat Transfer and Dielectric Properties: Achieve excellent thermal management and dielectric insulation, which can be leveraged in EV cooling applications.
- **High Biogenic Content:** Choose an environmentally friendly option that has a higher biogenic content compared to many synthetic diester or polyol esters.
- **Cost-Effective:** Save more due to lower cost per unit volume. Molecular design leads to significant lower density compared to standard esters.

EsterTec VSP sets the standard for a new class of polyol ester that delivers a blend of high performance, efficiency, sustainability and outstanding value.

- Wide Temperature Operating Range: Reliable operation from -40°C to 200°C, enhancing low temperature viscometrics and high temperature stability.
- Enhanced Friction and Wear Control: Improved protection for components, reducing maintenance costs and downtime.
- **Energy Efficiency:** Lower energy consumption, translating to significant savings over time.
- **Environmentally Friendly:** A sustainable choice for next-generation lubricant formulations.

EsterTec excels in numerous fields of application, delivering exceptional performance, value, and reliability across various industries, including:



Superior Performance

EsterTec VSP esters can be used to optimize premium synthetic lubricant formulations for use in high-performance applications. Technical and economic benefits include:

Oxidative Stability	Resists degradation at high temperatures, minimizing deposits and sludge formulation; noncorrosive to iron, aluminum, or copper.
Hydrolytic Stability	Remains stable and effective even in the presence of moisture from condensation or contamination; achieves effective long-life performance in aqueous metalworking fluids.
Friction/Wear Reduction	Minimizes energy losses due to friction, improving energy efficiency.
Energy Efficiency	Low density that leads to decreased pumping energy requirements and reduced weight in mobile applications; helps conserve energy usage compared to standard lubricants.
Cost-Effectiveness	Affords favorable total cost of ownership through its efficiency and performance results; lower density = lower shipping costs.
Eco-Friendliness	High biogenic content, readily biodegradable, and low aquatic toxicity, making EsterTec VSP esters the preferred choice for EAL formulations.

PERFORMANCE DATA

EsterTec VSP: Advanced Synthetic Lubricant Technology That Delivers Across Every Performance Metric

EsterTec VSP Products – ISO 15 to ISO 32

Product Name	ESTERTEC 2N-1416	ESTERTEC 2LN-1418	ESTERTEC 2G-1432
KV100, cSt	3.6	4.1	6.8
KV40, cSt	16	18	33
Viscosity Index	110	125	180
Pour Point, °C	-60	-40	-42
Density	0.895	0.893	0.890
Noack volatility, %	9	7	1
Biogenic Content, %	64	65	74
Oxidative Stability	\heartsuit	\bigotimes	\bigotimes
Hydrolytic Stability	\mathbf{i}	\bigotimes	\bigotimes
Friction/Wear Reduction	\bigotimes	\bigotimes	\bigotimes
Energy-Efficiency Advantage	\bigotimes	\bigotimes	\bigotimes
Cost/Performance Advantage	\bigotimes	\bigotimes	\bigotimes





Through its innovative molecular structure and production process, this synthetic lubricant component offers:

Superior Stability: Exceptional resistance to oxidation, thermal breakdown, and hydrolysis, for extended service life.

Excellent Control of Friction and Wear: A unique molecular design that enables a balance of polar attraction to metal interfaces and surface packing under EHL conditions that reduce the coefficient of friction.

Broad Operating Temperature Range: Lubricants formulated with VSP esters for cold temperature applications exhibit low dynamic viscosity and excellent pour point, ensuring reliable performance in extreme conditions. For high-temperature applications, VSP esters offer low volatility and a high flash point, enhancing product durability and safety. The excellent viscometric properties of EsterTec VSP contribute to improved energy efficiency, making them the ideal solution for demanding industrial, automotive, and dielectric applications.

EsterTec synthetic esters



ZSCHIMMER & SCHWARZ

Chemistry tailor-made

AMERICAS

- Zschimmer & Schwarz Inc.
 70 GA Highway 22 W
 Milledgeville, GA 31061, USA
 T +1 478 454 1942
 lubricants@zschimmer-schwarz.com
 zslubes.com
- Zschimmer & Schwarz do Brasil Ltda. Estrada Geral Morro do Paula 546 Distrito Industrial – Bairro São Borja 93032-530 São Leopoldo, BR T +55 51 3566 1666 zsb@zschimmer-schwarz.com.br zslubes.com

EUROPE

Zschimmer & Schwarz Italiana S.p.A. Via Angelo Ariotto, 1/C 13038 Tricerro (VC), IT T +39 0161 808 111 info.zsi@zschimmer-schwarz.com zslubes.com

> Zschimmer & Schwarz España S.p.A.

Carretera CV-20 km 3,200. Apdo. 118 Vila-Real (Castellón) 12540, ES T + 34 964 62 63 65 info.zse@zschimmer-schwarz.com zslubes.com

Zschimmer & Schwarz GmbH & Co KG Max-Schwarz-Straße 3-5

56112 Lahnstein, DE T +49 2621 12-0 info@zschimmer-schwarz.com zschimmer-schwarz.com

ASIA

Zschimmer & Schwarz Chemical (China) Co., Ltd. No. 16, Kaiyuan Road Datang Industrial Park Sanshui, 528143 Foshan, Guangdong, CNT +86 757 87 27 06 01 zsc@zschimmer-schwarz.cn zschimmer-schwarz.com