


NOTE:  
1. REMOVE JUMPER JA TO PREVENT HANDSWITCH INITIATED MOTION

TERMINAL BLOCK CONFIGURATION JUMPERS:  
JUMPERS J1 AND J2 ARE REQUIRED, J3 IS OPTIONAL

	J1	J2	J3
* <input type="checkbox"/> STANDARD (RET INCR SIG)	D-M	F-N	
<input type="checkbox"/> STANDARD (EXT INCR SIG)	D-N	F-M	
<input type="checkbox"/> REVLOS			E-F
<input type="checkbox"/> FWDLOS			E-D



17-5117-110 -

SIZE:  
**A**

THIS DOCUMENT IS A COPY AND IS NOT THE SOURCE DOCUMENT. INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTICE. THE INFORMATION CONTAINED HEREIN IS COPYRIGHTED BY HAROLD BECK AND SONS, INC. CHANGES TO THE DOCUMENT ARE PROHIBITED. CONTACT A BECK SALES ENGINEER IF A CERTIFIED DRAWING IS REQUIRED.

**HAROLD BECK & SONS INC**  
NEWTOWN INDUSTRIAL COMMONS    NEWTOWN, PENNSYLVANIA 18940    USA

TITLE:  
**WIRING DIAGRAM GROUP 14-XX7**  
**120 VOLT 2 AUX SWITCHES 1 POTENTIOMETER**  
**EXT/RET**

DRAWN: CHH 10-12-07	SCALE: NONE	DRAWING NO: <b>17-5117-110</b>	REV: -
CHECKED: GMD 10/15/07			
APPROVED: JHM 10/16/07		SHEET NO.    1    OF    1	